

Ottica Sortie Cylindrical Edge-lit Sortie (Aluminum)

Job/Location: _____

Contractor: _____ Prepared By: _____

Model Number: _____ Date: _____



INTERNAL SPECIFICATIONS

AC ONLY, AC/DC and SELF-POWERED: comes standard configured with high-output LED technology and 120/347VAC input. Nickel-cadmium batteries provide a minimum 30 minutes of emergency duration. Solid state charger & transfer. CSA 22.2 No. 141 Performance Certified. **OTTICA SORTIE** configured for AC/DC operation feature a 2 wire universal DC input; 6VDC - 24VDC backup voltages are standard.

EXTERNAL SPECIFICATIONS

The **OTTICA SORTIE** series cylindrical housing is constructed as a single piece from extruded aluminum. The canopy is made from sturdy die-cast aluminum and the end caps from machined aluminum. The high clarity acrylic faceplate is available in both single face or double face versions, with a clear, white or mirrored background (please specify). White, baked powder coat finish is standard on all versions. Available in custom colours and finishes (please specify). External LED monitor light and test switch are standard on self-powered versions.

ORDERING INFORMATION

Series	Operation	Light Source	Mounting	Letter Colour	Face #	Chevrons	Options
OT-S (Sortie)	Blank (AC only)	L (LED)	WC (Wall & Ceiling)	ROC (Red on clear - single face only)	1 (Single)	U (Field adjustable chevrons)	OV (Oval shaped face)
	SP (Self-powered)		E (End)	ROW (Red on white)	2 (Double)		CC (Custom colour - specify)
				ROM (Red on mirror)			BA (Brushed aluminum finish)
							PA (Polished aluminum finish)
							SW (Special wording - specify)
							PK12 (12" pendant kit)
							UDC (Universal 6 - 24VDC)
							90SP (90 min. emergency)
							120SP (120 min. emergency)


EXAMPLE: OT-S-L-WC-ROM-1-U

DESCRIPTION: Ottica edge-lit sortie, 120/347VAC input, AC only, red LED, wall / ceiling mount, red on mirror, single face, universal chevrons



INDOOR ARCHITECTURAL EXITS

DIMENSIONS (MM, IN.)



Wall & Ceiling Mount



End Mount



Ottica Oval

Model	A	B	C	D	E	F
Wall	18" (457mm)	10 ^{9/50} " (259mm)	2" (51mm)	4 1/2" (406mm)	9" (229mm)	3" (76mm)
Ceiling	18" (457mm)	10 ^{3/20} " (258mm)	2" (51mm)	4 1/2" (394mm)	9" (229mm)	
End	14 1/2" (368mm)	10" (254mm)	2" (51mm)			

MODERN DESIGN

The **OTTICA SORTIE** series of cylindrical designed edge-lit sortie signs feature a radical, high-tech look. The design lends cutting edge technology and style to today's modern interior sortie sign applications. The one-piece cylindrical body is extremely rigid and holds all of the LED circuitry in precision formed mounting channels. The indirect LED illumination provided by this design evenly lights the acrylic face with crisp, even light. The clear area of the ultra thin faceplate virtually disappears once installed. The choice of clear, white or mirrored backgrounds allows the sign to be best matched to the decor. A wide variety of finishes and mounting configurations available will ensure that the **OTTICA SORTIE** can be suited to your installation.

MECHANICAL SPECIFICATIONS

The **OTTICA SORTIE** cylindrical housing is constructed of sturdy extruded aluminum. All mounting channels are extruded with the housing at the time of manufacture, adding to the rigidity of the sign. The housing end caps are machined from solid aluminum and secured to the housing with a centered screw. The **OTTICA SORTIE** canopy is made from die-cast aluminum and is attached to the housing at the factory to provide the most secure mounting possible. The **OTTICA SORTIE** is supplied standard with a durable white, baked powder coat finish. Other colours are available, including custom colour matching, please specify. Faceplates for the **OTTICA SORTIE** are constructed of high clarity, solid acrylic. Field removable directional chevron arrows are standard. Custom wording / graphics are available, please specify.

BATTERY TECHNOLOGY

The **OTTICA SORTIE-SP** is designed with a maintenance free, nickel-cadmium battery providing a minimum emergency duration of 30 minutes. Recharge time of the battery is twenty-four [24] hours.

SELF-POWERED VERSIONS

The **OTTICA SORTIE-SP** self-powered series is designed to operate on battery power in the event of a power failure. Both the battery and charger are completely contained within the standard enclosure. There are no external components and no alterations made to the external dimensions of the standard sign. The **OTTICA SORTIE-SP** self-powered series utilize a solid state transfer technology that eliminates the possibility of relay failure due to particle build up on the relay. Status is easily determined via an LED that indicates AC-ON. A push button test switch allows maintenance personnel to quickly confirm the operational status of the sortie sign on AC fail.

ELECTRICAL SPECIFICATIONS

The **OTTICA SORTIE** series is configured with high-output LED lamps. Standard with 120/347VAC input. All LED versions are C860 approved and consume only 2W nominal power. Optional UDC emergency illumination is provided by the LED light source at the following wattages: 6VDC - 24VDC, 2 watts

INSTALLATION

The **OTTICA SORTIE** is suitable for wall & ceiling (includes sloped ceiling) or end mounting. Suitable for indoor installations.